



<b>MATERIAL</b>	QUARTZITE	<b>WEIGHT</b>	6.50 LBS PER SF 34.97 LBS PER PC
<b>ORIGIN</b>	CHINA		
<b>FINISH</b>	SNAP CUT	<b>CRATE QTY</b>	22 PCS
<b>JOINT SYSTEM</b>	INTERLOCKING		
<b>PART NUMBER</b>	QRTDESGLDFLAG538	<b>COLOR</b>	SAGE GREEN, LIGHT RUST, BEIGE
		<b>GROUT LINE</b>	GROUT REQUIRED
<b>DIMENSIONS</b>	5.38 SQ PER PC	<b>APPLICATIONS RESIDENTIAL</b>	EXTERIOR, INTERIOR, WALLS, FLOORS, FACADES FEATURE WALLS, FIREPLACES, CHIMNEYS, RETAINING WALLS, STONE PILLARS, STONE COLUMNS, POOL SURROUNDS, WALKWAYS, ENTRIES, PATIOS, STAIRS
<b>THICKNESS</b>	1/2"		
<b>SOLD BY</b>	CRATE - 118.36 SF	<b>APPLICATIONS COMMERCIAL</b>	EXTERIOR, INTERIOR, HOSPITALITY, RETAIL, LANDSCAPE
<b>UOM</b>	SF		

**WARNING: READ PRIOR TO INSTALLATION:**

Natural stones are products of nature and are prone to variations in color, texture, shading and veining that may differ from displays. Variations are not considered flaws as no two pieces of stone are alike. Prior to installation, ensure enough material, including waste is purchased for the entire project. Mix product from various cartons, and lay out all tiles and coordinating pieces to ensure optimal blending prior to installation. Natural stone products should be sealed prior to grouting. NO CLAIMS WILL BE ACCEPTED AFTER THE MATERIAL HAS BEEN INSTALLED



<b>MATERIAL</b>	QUARTZITE	<b>WEIGHT</b>	6.00 LBS PER SF 21.84 LBS PER PC
<b>ORIGIN</b>	CHINA		
<b>FINISH</b>	TUMBLED	<b>CRATE QTY</b>	36 PCS
<b>JOINT SYSTEM</b>	INTERLOCKING		
<b>PART NUMBER</b>	QRTDESGLDFLAG364T	<b>COLOR</b>	SAGE GREEN, LIGHT RUST, BEIGE
		<b>GROUT LINE</b>	GROUT REQUIRED
<b>DIMENSIONS</b>	3.64 SQ PER PC	<b>APPLICATIONS RESIDENTIAL</b>	EXTERIOR, INTERIOR, WALLS, FLOORS, FACADES FEATURE WALLS, FIREPLACES, CHIMNEYS, RETAINING WALLS, STONE PILLARS, STONE COLUMNS, POOL SURROUNDS,
<b>THICKNESS</b>	1/2"		WALKWAYS, ENTRIES, PATIOS, STAIRS
<b>SOLD BY</b>	CRATE - 131.04 SF	<b>APPLICATIONS COMMERCIAL</b>	EXTERIOR, INTERIOR, HOSPITALITY, RETAIL, LANDSCAPE
<b>UOM</b>	SF		

**WARNING: READ PRIOR TO INSTALLATION:**

Natural stones are products of nature and are prone to variations in color, texture, shading and veining that may differ from displays. Variations are not considered flaws as no two pieces of stone are alike, Prior to installation, ensure enough material, including waste is purchased for the entire project. Mix product from various cartons, and lay out all tiles and coordinating pieces to ensure optimal blending prior to installation. Natural stone products should be sealed prior to grouting. NO CLAIMS WILL BE ACCEPTED AFTER THE MATERIAL HAS BEEN INSTALLED