



<b>ITEM NAME</b>	BIANCO DOLOMITE - 5/8X1-1/4 BRICK	<b>PART NUMBER</b>	MARBIADOLBR58H
<b>CATEGORY</b>	MARBLE	<b>FORMAT/ TYPE</b>	MOSAIC
<b>FINISH</b>	HONED	<b>UOM</b>	PIECE
<b>DIMENSIONS</b>	12 x 12	<b>THICKNESS</b>	3/8"
<b>SQFT P/SHEET</b>	1.00 SF	<b>PIECE SIZE</b>	5/8 x 1-1/4
<b>COLOR</b>	WHITE, LIGHT GREY		
<b>APPLICATIONS</b>	RESIDENTIAL, COMMERCIAL FLOORS/WALLS, INTERIOR/EXTERIOR (NO FREEZE/THAW), (NO STEAM SHOWER), WET AREA (WHEN PROPERLY SEALED), (NO POOLS)		

**WARNING: READ PRIOR TO INSTALLATION:**

Natural stones are products of nature and are prone to variations in color, texture, shading and veining that may differ from displays. Variations are not considered flaws as no two pieces of stone are alike, Prior to installation, ensure enough material, including waste is purchased for the entire project. Mix product from various cartons, and lay out all files and coordinating pieces to ensure optimal blending prior to installation. Natural stone products should be sealed prior to grouting. NO CLAIMS WILL BE ACCEPTED AFTER THE MATERIAL HAS BEEN INSTALLED



<b>ITEM NAME</b>	BIANCO DOLOMITE - 5/8X1-1/4 BRICK	<b>PART NUMBER</b>	MARBIADOLBR58P
<b>CATEGORY</b>	MARBLE	<b>FORMAT/ TYPE</b>	MOSAIC
<b>FINISH</b>	POLISHED	<b>UOM</b>	PIECE
<b>DIMENSIONS</b>	12 x 12	<b>THICKNESS</b>	3/8"
<b>SQFT P/SHEET</b>	1.00 SF	<b>PIECE SIZE</b>	5/8 x 1-1/4
<b>COLOR</b>	WHITE, LIGHT GREY		

**APPLICATIONS**

RESIDENTIAL, COMMERCIAL

FLOORS/WALLS, INTERIOR/EXTERIOR (NO FREEZE/THAW), (NO STEAM SHOWER), WET AREA (WHEN PROPERLY SEALED), (NO POOLS)

**WARNING: READ PRIOR TO INSTALLATION:**

Natural stones are products of nature and are prone to variations in color, texture, shading and veining that may differ from displays. Variations are not considered flaws as no two pieces of stone are alike, Prior to installation, ensure enough material, including waste is purchased for the entire project. Mix product from various cartons, and lay out all files and coordinating pieces to ensure optimal blending prior to installation. Natural stone products should be sealed prior to grouting. NO CLAIMS WILL BE ACCEPTED AFTER THE MATERIAL HAS BEEN INSTALLED